



FY - 1600SE

Liner-less Laminator

Single Hot Liner-less Laminator

Professional sturdy and robust laminator designed to guarantee every day high quality result with great speed (on demand up to 15m/min).

64" ALUMINUM SHAFTS (total 6 shafts) for easy loading and unloading of the rolls.

It can support big and heavy rolls with diameter up to 200mm(8in.) thanks to the increased distance between rollers and support shafts.

Heated upper roller with preset electronic temperature regulation - standard on FAYON 1600 model (Room ~ 60° C)

Anti-crushing safety photosensitive device with emergency stop button.

Pulling film rod, allowed using the low cost liner-less film.

TECHNICAL PARAMETER

| Model | FY-1600SE |
|--------------------------|--------------|
| Max laminating width | 1620mm |
| Max laminating thickness | 35mm |
| Max Speed | 15m/min |
| Max temp. | Room~60 C |
| Heating | Infrared |
| Preheating time | 10~15 min |
| Roller upgrade | Air Cylinder |
| Power Input | 0.8~1.0kw/h |
| Volt | 110/220V |
| Roller material | Silicon |
| N.W | 250kg |

*Subject to change without prior notice.

CONTROL PANEL FUNCTION

- hot/ cold switch;
- setting temperature room~60°C;
- changing language(Chinese, English, Spanish);
- auto-continue/manual-jogging laminating model switch;
- laminating speed adjust(0~9levels)

