



Digital Inkjet Printing Equipments Manufacturer

www.floradigital.com.cn

Flora XTRA2000HUV High-res UV Hybrid flatbed Printer



Anti-crash Sensor




Automatic Height Adjust System



Vacuum Conveyer-belt System



Industrial Take up & Feeding System



Belt automatic deviation correction function



Dual Negative Pressure System



- Variable color configuration, standard 4 color plus white optional
- Grayscale print heads, variable drop size from 6 to 18pl
- Speed up to 100 sqm/hr
- Handles flexible and rigid substrate up to 2m, and 5.1cm thick
- Vacuum belt driving with 8 vacuum zones
- White ink and CWC print capability solution

TECHNICAL SPECIFICATIONS

Print Head	4~12 KM1024I print heads						
Drop Size	6 ~ 18 picolitre						
Resolution	Up to 726 x 1440 dpi						
Productivity	<table border="0"> <tr> <td>Production Mode</td> <td>100 sqm/hr</td> </tr> <tr> <td>Quality Mode</td> <td>70 sqm/hr</td> </tr> <tr> <td>Ultra Quality</td> <td>50 sqm/hr</td> </tr> </table>	Production Mode	100 sqm/hr	Quality Mode	70 sqm/hr	Ultra Quality	50 sqm/hr
Production Mode	100 sqm/hr						
Quality Mode	70 sqm/hr						
Ultra Quality	50 sqm/hr						
Ink Configuration	4, 6, 8 colors for option, C+M+Y+K, C+M+Y+K+W+V, C+M+Y+K+Lc+Lm						
Print Technology	Piezoelectric inkjet, Grayscale Technology						
Ink Types	LED UV inks						
Ink Cartridge Size	1.5 liter						
Image Process Software	Photoprint Flora Edition 12,						
Color Management	ICC based color, adjustment curves, density adjustment						
File Format	Tiff, Jpeg, Postscript, EPS, PDF, etc						
Media							
Handling	Vacuum table convey-belt movement, rigid flexible printing capability material						
Rigid Media Support	Standard convey-belt table support rigid materials up to 200cm width						
Rolling Media Support	Max. print width up to 200cm, diameter 30cm						
Thickness	Up to 51mm						
Connectivity							
Interfaces	USB 3.0						
Curing System							
	Dual LED UV curing system, separated adjustable power.						
Dimensions							
Printer	430x 100 x 155cm						
Shipping	460 x 115 x 180cm						
Weight	1500KG						
Operating Conditions							
Temperature	20 to 30°C						
Relative Humidity	35% - 65%, non-condensing						
Electricity Request							
Power	5000W						
Requirement	Input voltage: 2.00 to 240VAC, single-phase, 50/60Hz, 25A						
Air	0.6-0.8Mpa						
Warranty	One year limited warranty						

*Subject to change without prior notice.